

PRX15 – The powerful ProxReader

Proximity components by deister electronic have gained worldwide recognition for superior performance in many applications.

Innovative design has made these products exceptionally compact providing the highest level of security and reliability, even in hostile environments.



PRX15

The compact, yet powerful PRX15 integrated reader provides user friendly door and vehicle barrier control for areas that demand longer reading distances.

Your benefits at a glance

- Compatible with most of the existing access control systems
- Low power consumption 24 V/DC, 500mA
- Audible and visual feedback for easy and safe system operation
- Easy to install as electronic and antenna are in the same housing
- **Rugged design** and a tamper switch provide a high level of protection against vandalism and the elements
- SCF-Synchronization Function enables the operation of two or more readers very close to each other without interference
- ATF Auto Trim Function is developed exclusive by deister electronic (optional)
- It adjusts the reader automatically to its operating environment for best performance

Technical Data

Dimensions (mm): $300 \times 300 \times 30$

Installation: surface mounted on non

metal surface

Housing material: ASA

Power consumption: $24V/DC \cdot < 500 \text{ mA}$

(linear regulated)

Operating frequency: 125 kHz

Electrical protection: Reverse polarity and transient

protection

Protection: IP 54 (IEC 529), depend-

ing on mounting type

Operating temperature: $+5^{\circ}\text{C}$ to $+60^{\circ}\text{C}$

optional: $-25^{\circ}\text{C} \text{ to } +60^{\circ}\text{C}$

Reading distance: up to 600 mm, depending

on mounting and trans-

ponder type

Interfaces: Open Collector

Protocol: Wiegand, Data/Clock,

Magstripe, RS232/485

Data formats: up to 64 bit user pro-

grammable data formats

Connection: 10-pin screw terminal

connector

Tamper protection: switch inside housing

ATF: optional

