

deister electronic provides high-end technology for guarding, maintenance and facility management markets.

Thanks to an ongoing innovation process dataLog® has developed into standard solution for all applications where checkpoints and service information are to be managed with a high grade of efficiency.

Duostar

The Duostar data collector reads both barcode and proximity checkpoints in a very handy and user-friendly unit. Only validated readings are stored for evaluation. Audible and optical feedback provides immediate indication to the user of a successful reading.

The Duostar is fully compatible with systems using either the deProx or deWatch data collector, including the deTrans and deReporter data transfer unit. The Duostar is supported by the full range of deister electronic evaluation software.

Your Advantages at a Glance

- **Reads infrared** barcode and proximity checkpoints
- **Backwards compatible** to existing deister electronic systems
- **Designed for mobile use and harsh environments**
- **Compact and Simple to use**
- **Optical and audible feedback**
- **Standard batteries**, for easy replacement
- Also available as **intrinsically safe version**

Duostar – the Data Collector



Technical data

dimensions:	45 x 175 x 36 mm
power supply:	2 AA batteries
material:	Polycarbonate, black
protection class:	IP 54
weight:	approx. 200 g
memory capacity:	4000 readings

Accessories

Leather case, Nylon case

for safe storing of the data collector during the guard tour.

Screwdriver Snake-Eye

special screw driver for battery case

Suitable Checkpoints

Proximity Checkpoints KSC

Barcode Checkpoints KSI, KSB etc.



Suitable Data Transfer Units

de Trans, de Reporter